

## VueSlide 130LS Sliding Door

# Specifications

**Vueglide** - push up to 300kg with two fingers

**Colours** - Polyester powder coated textured paint available in any RAL colour to a standard 60 microns finish.

**Vuelock** - Siegenia 4 point locking is secure and burglar resistant. Tested to RC2 (EN1627-1630) standard

10 yr Guarantee\*

**Vuetight** - Interlocking weather - seal - keeps bad weather out - even around the hinges

Stainless steel rollers - robust and durable

Teflon coated gaskets - dirt doesn't stick

Hand engineered and finished - All joints are finished with a 2 part adhesive for extra strength  
Slim sightlines Narrow (69mm) or Standard (98mm)

Slim sightlines - Narrow (69mm) or Standard (98mm)

Lift and slide operation

Dual or Triple rail slider

Outerframe - Depths 139mm (Dual rail) & 210mm (Triple Rail)

Low threshold - level off floors without compromising on weather performance 3 options (Low, Standard, Enhanced)

Maximum Height per panel 2700mm, width variable on other options.

Maximum glass weight 300kg per panel

U values from as low as 1.38 W/m<sup>2</sup>k

Wind load - tested to 1200pa

Airtightness - (to EN12207) 600pa

Watertightness - (to EN12208) up to 750 pa

Glazing - can accommodate sealed units up to 42 mm

Luxury handles in 8 finishes

Standard handles in a choice of silver, black, white and RAL colours

Fibreglass reinforced polyamide breaks for enhanced thermal performance - UF value of 2.35 w/m<sup>2</sup>k.